



**Putzmeister**

## Your benefits

- Maintenance and service-friendly: everything is protected below the canopy
- Operating panel ergonomical on one side
- Large hopper 280 l with rubber collar and protective grid
- Piston pump unit extremely robust
- Chassis for road use
- Supporting feet for secure stability
- Fine grained concrete up to 32 mm grain size
- Made in Germany

## P 718 – Low-wear, compact powerhouse



The P 718 piston pump is ideally suited for conveying fine concrete up to a grain size of 32 mm and for working with shotcrete.

It is our most powerful machine of this kind to date – it boasts impressive performance data and is lightweight with a well thought-out and user-friendly design.

Your expert Putzmeister dealer will be happy to explain the additional advantages to you and answer all your questions with regard to your individual requirements.

Shotcrete

- **Shotcrete**



Fine grained  
concrete

- **Fine grained concrete  
up to 32 mm grain size**





Fine concrete pumps like the P 718 are among the most versatile systems. You can use them for shotcrete or for pumping fine concrete of up to 32 mm.



All maintenance and service areas can be accessed quickly and conveniently inside the clearly organised and easily accessible engine compartment.



The P 718 is operated entirely from one side: For example, the infinitely variable adjustment of the delivery rate or the engine speed

## Technical data

### P 718 TD / SD

### P 718 TE / SE

<b>Feed hopper</b>	360 l (with rubber collar)	
<b>Theoretical delivery rate*</b>	4–17.4 m <sup>3</sup> /h	4–17.4 m <sup>3</sup> /h
<b>Delivery pressure</b>	68 bar	68 bar
<b>Delivery range**</b>	max. 300 m horizontal and 100 m vertical; fine grained concrete, max. 100 m horizontal and 80 m vertical	
<b>Piston pump</b>	Hydraulic, 2-cylinder	
<b>Cylinder diameter</b>	150 mm	150 mm
<b>Drive</b>	3-cylinder Deutz diesel engine, 34.5 kW	30 kW electric motor, 400 V, 50 Hz
<b>Drive cylinder diameter</b>	80/45 mm	80/45 mm
<b>Piston stroke</b>	700 mm	700 mm
<b>Strokes/min</b>	27	27
<b>Weight</b>	2320 kg (TD) / 2000 kg (SD)	2260 kg (TE) / 1940 kg (SE)
<b>Length × width × height</b>	4644 × 1560 × 1790 mm (TD) 3025 × 1460 × 1600 mm (SD)	4644 × 1560 × 1750 mm (TE) 3025 × 1460 × 1450 mm (SE)
<b>Filling height</b>	1180 mm (TD) / 1120 mm (SD)	1180 mm (TE) / 1120 mm (SE)
<b>Maximum particle size</b>	32 mm	32 mm
<b>Machine model</b>	Trailer pump (TD and TE), Stationary pump (SD and SE)	
<b>Chassis</b>	T chassis (TD and TE), runner (SD and SE)	

\* The delivery rate is theoretical and depends on the pump pressure.

\*\* The data is based on experience and is dependent on the materials used.

## Equipment

Car fuse	■
Clamp coupling with sealing 4,5"	■
Cleaning tool	■
Instruction manual and spare parts list	■
Protective grid	■
Protective helmet	■
Rubber collar	■
Tool box with tool	■
Vibrator	■
Additive metering	□
Air vessel (self levelling floor screed)	□
Cable remote control	□
Central lubrication system	□
Chassis 2,5 t	□
Customer labelling	□
Exhaust flap	□
Flushing water pump	□
High-pressure cleaner	□
Lifting eye	□
Light holder 24 V	□
Particle filter	□
Radio remote control	□
Special canopy paint in RAL colours	□
Stroke counter	□
Working light	□
Zero report for hopper	□

□ Option    ■ Standard

## Putzmeister Mörtelmaschinen GmbH

Max-Eyth-Straße 10 · 72631 Aichtal / Germany  
P.O.Box 2152 · 72629 Aichtal / Germany  
Tel. +49 7127 599-0 · Fax +49 7127 599-743  
mm@pmw.de · www.pmmortar.de



# Putzmeister